ZJTEX ELECTRIC MOTOR BUSINESS GROUP

37JB6K/EG530-0645 PM DC gear motors

Motor Technical Data Rated voltage **TYPE** No-load speed Rated speed Rated torque Output power Rated current Stem current **VDC** r/min r/min W mΑ g.cm EG530-0645 6 4500 4000 0.45 ≤160 1.3 11


Gear Motor Technical Data Reduction ratio 400 750 1000 1500 100 150 200 250 300 500 3000 Number of gear trains 4 5 5 5 5 6 6 6 7 7 6 Efficiency 66 59 59 59 59 48 48 48 48 43 43 No-load speed r/min 45 30 22.5 18 15 11 9 6 4.5 3 1.5 Rated speed r/min 40 27 20 10 8 5 4 2.7 1.4 16 13 Rated torque kg.cm 0.7 1.0 1.3 1.6 1.9 2.1 2.6 4.0 5.3 6 6 kg.cm 12 18 18 18 18 18 18 18 18 18 18 Max permissible load in a short time Direction of Rotation **CCW CCW CCW** CW CW CW CW CW **CCW CCW** CW

Use condition

Temperature of condition : -10~+50 °C Comparatively humidity: <85%(25 °C)

Figure

(1) Index of speed allow error ± 10%(2) Can making other characteristics motor



Reduction ratio L
50 ~ 100 24
120 ~ 300 26.5
350 ~ 1000 29
1500 ~ 3000 31.5

